

40-80W IND Series Wall Pack



Project:

Type:

Catalog#:

Description

START Lighting's LED Wall Packs are high performance, durable and reliable outdoor luminaires. LED Wall Pack lighting fixtures are ideal for improving light on building exteriors, doorways and walkways.

Features & Benefits

- Low profile Canopy Luminaire
- Isolated integral driver
- High Efficacy LED chipset / 50,000 hour lifespan
- Consumes up to 75% less energy than standard mercury vapor lamps
- Rugged IK07 Rated
- IP65 Wet Location Rated
- Minimized labor costs
- LM79/LM80/TM-21 data available
- Working Temp: -10° F to 120° F
- 105° Beam Angle
- Minimized labor costs
- LM79/LM80/TM-21 data available
- Motion sensor available. Consult factory.

SPECIFICATIONS	DETAILS		
Model	BINWP-W48D-50	BINWP-W60D-50	BINWP-W80D-50
Input Power (W)	48	60	80
Power Input Voltage	120-277VAC		
Delivered Lumens (lm)	5,280	6,600	8,800
Power Factor	≥0.95		
CRI	>80		
Color Temperature (K)	5000K		
Dimming	Non-Dimmable		
Certification	UL, RoHS, FCC, DLC		
Material Compliance	RoHS Compliant, Contains no Mercury		
Application Rating	Outdoor Use / IP65 Wet Location Rated		
Mounting	Surface J-box Mount Standard		
Operating Temperature	-10°F to 120°F		
Beam Angle / Lens	105° Beam Angle / Prismatic		
Hour Lifetime (L70)	50,000		
Warranty	5 Years		

*Dimensions and specifications subject to change without notice.

40-80W IND Series Wall Pack

40-80W IND Series Wall Pack Ordering

Model Number	DETAILS	Watts	CCT	Inventory Status
BINWP-W48D-50	Industrial Wall Pack Luminaire: 48W, 105°, 5000K	48	5000	Stock Item
BINWP-W60D-50	Industrial Wall Pack Luminaire: 60W, 105°, 5000K	60	5000	Stock Item
BINWP-W80D-50	Industrial Wall Pack Luminaire: 80W, 105°, 5000K	80	5000	Stock Item

40-80W IND Series Wall Pack Options

Model Number	DETAILS	Inventory Status
Sensor Options	Photocell- Optional	To Order

40-80W IND Series Wall Pack Dimensions & Weight

Model	A (Length)	B (Height)	C (Depth)	Weight (lbs)
48-80W Industrial Wall Pack Luminaire	15.75"	13.00"	9.5"	7

