

LT Series Recessed Baffle Canless LED Downlights

HALO



**NO HOUSING
REQUIRED**
Repositionable driver j-box included



The LT Canless Series are all-purpose LED downlights designed to mount directly to ceilings – no housing required. Install into remodel or use canless mounting frames/plates for new construction applications. Flip the switch to select between 5 color temperatures from soft white (2700K) to daylight (5000K) and discover the perfect color temperature lighting for any project. Fixtures offer a safe, non-conductive dead-front baffle and a regressed diffuse flat lens for low-glare downlighting. In addition to matte white baffle fixtures, smooth splay decorative overlays can be ordered in paintable matte white and matte black finishes.

**When you're looking for the ideal balance of features and affordability,
LT Series fixtures are the perfect choice.**

Product Features

- Round 3", 4", & 6" sizes available with baffle trims
- Smooth splay decorative overlays in paintable matte white or matte black (sold separately)
- No housing required - for remodel and new construction installations
- For new construction, use with canless mounting frames/plates
- Suitable for IC (insulation contact) or non-IC applications
- Matte white plastic non-conductive dead-front trim and regressed flat diffuse lens
- 5-Color Field-SeleCCTable™: 2700K, 3000K, 3500K, 4000K, 5000K; 90+ CRI
- Lumens: 3 in. - 550 lm; 4 in. - 650 lm, 6 in. - 750 lm (nominal)
- Dims to 10% (phase cut LE/TE); 120V input
- AIR-TITE, wet location-listed, IC-rated, and ENERGY STAR® certified
- 35,000 hrs of maintenance-free operation
- 5-year warranty



LEARN MORE



3"



4"



6"




Matte Black



Paintable Matte White

EASY CANLESS
INSTALLATION
Mounts directly to ceiling



Complete HALO LTC 5CCT LED Ordering Table

Catalog Number	Description	UPC	Accessories			
			Decorative Overlays	New Construction Mounting Frames	New Construction Smash Plate	Extension Cables
LTC305FS5B	3-inch LT Series Baffle Canless LED Downlight 550 lm, 90+ CRI, 5-color Field-SeleCCTable™: 27/30/35/40/5000K, 120V 60Hz, 10% LE/TE phase cut dimming, Matte White	080083297047	LT30MW 3" Smooth Splay Paintable Matte White LT30MB 3" Smooth Splay Matte Black	HL3RSMF 3" Round/Square Mounting Frame	SP346RS 3"/4"/6" Round/ Square Smash Plate	HLB06FSEC 6-ft. extension cable HLB12FSEC 12-ft. extension cable HLB20FSEC 20-ft. extension cable
LTC406FS5B	4-inch LT Series Baffle Canless LED Downlight 650 lm, 90+ CRI, 5-color Field-SeleCCTable™: 27/30/35/40/5000K, 120V 60Hz, 10% LE/TE phase cut dimming, Matte White	080083297061	LT40MW 4" Smooth Splay Paintable Matte White LT40MB 4" Smooth Splay Matte Black	MF4RC 4" Round Mounting Frame with 1/2" Drywall Collar HL4RSMF 4" Round/Square Mounting Frame		
LTC608FS5B	6-inch LT Series Baffle Canless LED Downlight 750 lm, 90+ CRI, 5-color Field-SeleCCTable™: 27/30/35/40/5000K, 120V 60Hz, 10% LE/TE phase cut dimming, Matte White	080083297085	LT60MW 6" Smooth Splay Paintable Matte White LT60MB 6" Smooth Splay Matte Black	MF6RC 6" Round Mounting Frame with 1/2" Drywall Collar		
LTC608B-MF6RC- 6PK	New Construction Kit: (6) 6-inch LT Series Baffle Canless LED Downlights + (6) New Construction Mounting Frames 6-inch LT Series Baffle Canless LED Downlight 750 lm, 90+ CRI, 5-color Field-SeleCCTable™: 27/30/35/40/5000K, 120V 60Hz, 10% LE/TE phase cut dimming, Matte White	080083297504		HL6RSMF 6" Round/Square Mounting Frame (Included)		



Refer to ENERGY STAR® Certified Products List. Can be used to comply with California Title 24 High Efficacy requirements. Certified to California Appliance Efficiency Database under JA8.
NOTE: Due to T20 changes as of July 1st 2019 consult factory for current catalog number and availability for T20 compliant products.



Cooper Lighting Solutions
1121 Highway 74 South
Peachtree City, GA 30269
P: 770-486-4800
cooperlighting.com

Canada Sales
5925 McLaughlin Road
Mississauga, Ontario L5R 1B8
P: 905-501-3000
F: 905-501-3172

© 2024 Cooper Lighting Solutions
All Rights Reserved
Publication No. BR51821824
October 2024

Product availability, specifications,
and compliances are subject to
change without notice.